

VS481B

4-Port 4K HDMI Switch







The VS481B is a 4-port video switch that enables fast switching between four HDMI sources, delivering up to 4K audiovisual content to a single HDMI display. It's an ideal addition to any AV setup where multiple video feeds need to be shared and switched instantly – perfect for home entertainment systems, meeting rooms, retail displays, and more.

Instant Switching between 4 HDMI Inputs

Enjoy a variety of video content by switching between 4 HDMI source devices, such as computers, media players, and more.







Pristine 4K Clarity

The VS481B supports Ultra HD resolutions up to 4K (3840×2160 @ 30Hz, 4:4:4), delivering crystal-clear detail.

Long-Distance 4K Transmission

The video switch supports flexible cabling, with connections to each HDMI source up to 3 meters ($\underline{2L-7D03H}$ recommended) and to the HDMI display up to 15 meters ($\underline{2L-7D15H}$ recommended), delivering optimal 4K visual clarity (4096 × 2160 / 3840 × 2160 @ 30Hz, 4:4:4) in any AV setup.



Flexible Switching Options

Switching is made easy with front-panel pushbuttons or the included IR remote control. Port selection can also be managed via a high-end controller, PC, or automation/theater software through an RS-232 serial connection to the switch. Or simply enable Auto Switch mode to automatically prioritize the most recently connected device as the video source.





The VS481B is well suited for any commercial or professional application requiring instant switching between multiple video sources for various viewing purposes.





Home Entertainment





Classroom





Meeting Room





Post Production

Previous Next

Commitment to Best Quality

Each product is rigorously tested under diverse environmental conditions to ensure high-quality, reliable, and cost-effective performance for our customers.





If you prefer to have ATEN contact you, please complete the form and a representative will be in touch with you shortly

First Name *	
Last Name *	
- Country *	1
Company *	
Email *	
Phone Number	
- Customer Type *]
Job Title *	

















10.2Gbps Max. Bandwidth

RS-232 Control

Switching

The VS481B 4-Port HDMI Switch allows you to quickly connect 4 HDMI sources to your HDMI display and easily switch between them via front panel pushbuttons, RS-232 or IR remote control. The front panel's LEDs indicate the source device selected for the display at a glance.

The VS481B supports Ultra HD 4Kx2K, the newest resolution for high definition displays; Auto Switching modes for auto port selection; Instant Switching for a smooth video transition between HDMI ports with increased efficiency; and features a built-in bi-directional RS-232 serial port that allows the switch to be controlled through a high-end controller, PC, and/or home automation/home theater software package.

- Allows up to four HDMI A/V sources to be connected to one HDMI display

 Quick and easy switching between HDMI sources via front panel pushbuttons, RS-232 or IR Remote control

 Supports 340MHz bandwidth for ultrahigh 4kx2k video

 HDMI (3D, Deep Color, 4kx2k); HDCP compatible

 Auto switching modes for auto port selection

 Long distance transmission up to 15 m (24 AWG)

 Consumer Electronics Control (CEC) support

 Supports Dolby True HD and DTS HD Master Audio

 Built-in bi-directional RS-232 serial remote port for high-end system control

 Instant switching between HDMI input sources

 Supports IR extension using a IR extension cable *

 LED indication of video source devices

Note: The IR extension cable (Part No. 2XRT-0003G) is not included inthis package.




Specifications

Specifications			
Video Input			
Interfaces	4 x HDMI Type A Female (Black)		
Impedance	100 Ω		
Max. Distance	3m @3840x2160@30 (4:4:4)		
Video Output			
Interfaces	1 x HDMI Type A Female (Black)		
Impedance	100 Ω		
Max. Distance	15m @3840x2160@30 (4:4:4)		
Video			
Max. Data Rate	10.2 Gbps (3.4 Gbps per lane)		
Max. Pixel Clock	340 MHz		
Compliance	HDMI (3D, Deep Color, 4K) HDCP Compatible Consumer Electronics Control (CEC)		
Max. Resolution	Up to 4096 x 2160 / 3840 x 2160 @ 60Hz (4:2:0); 4096 x 2160 / 3840 x 2160 @ 30Hz (4:4:4)		
Control	Control		
RS-232	Connector: 1 x DB-9 Female (Black) Baud Rate and Protocol: Baud Rate: 19200, Data Bits: 8, Stop Bits:1, Parity: No, Flow Control: No		
IR	1 x Mini Stereo Jack Female (Black)		
Connectors			
Power	Connector: 1 x DC Jack		
Power Consumption	DC5V:1.76W:8BTU/h		
	Note: The measurement in Watts indicates the typical power consumption of the device with no external loading. The measurement in BTU/h indicates the power consumption of the device when it is fully loaded.		
Environmental			
Operating Temperature	0 - 50°C		
Storage Temperature	-20 - 60°C		
Humidity	0 - 80% RH, Non-Condensing		
Physical Properties			
Housing	Metal		
Weight	0.48 kg (1.06 lb)		
Dimensions (L x W x H)	20.00 x 8.25 x 2.50 cm (7.87 x 3.25 x 0.98 in.)		
Carton Lot	10 pcs		
Note	For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.		



Diagram



ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan Phone: 886-2-8692-6789 Fax: 886-2-8692-6767

www.aten.com E-mail: marketing@aten.com

