

VS82

Splitter - placca a parete - (plastica) VGA 2-porte (250MHz)



The VS82 Video Splitter duplicates the video signal from an input source (i.e. a computer) and route it to up to 2 display devices (monitors, projectors, etc.). However, they go beyond being merely duplicators, in that they also enhance the video signals over distances up to 30 meters. Furthermore, they can be cascaded three levels to additional ATEN video splitters to support many numerous display devices. And they mount inconspicuously on the wall or out of sight.

Caratteristiche

- One video input to 2 video outputs.
- Cascadable to 3 levels - provides up to 8 video signals.
- Supports up to 250 MHz bandwidth.
- Long distance transmission - up to 30 m (210')*.
- High video resolution - up to 1920 x 1440.
- DDC, DDC2, DDC2B Compatible (Port 1 only).
- Compact design with convenient topside connection, lays flat on a desktop or mounts on the wall.
- Supports VGA, XGA, SVGA, UXGA and multisync monitors.
- OS Support: Windows 2000, Windows XP, Linux, Mac and Sun

* I contenuti video trasmessi a distanze molto lunghe attraverso un cavo VGA potrebbero subire un lieve degrado del segnale e della qualità del video.

Specifiche

Ingresso video	
Interfacce	1 x HDB-15 maschio (blu)
Distanza max.	1,8 m
Impedenza	75 Ω
Uscita video	
Interfacce	2 x HDB-15 femmina (blu)
Impedenza	75 Ω
Video	
Larghezza di banda max.	250 MHz
Risoluzione max.	Fino a 1920 x 1440
Distanza max.	Fino a 30 m
Connettori	
Alimentazione	1 x Connettore CC
Consumo	DC9V:1.02W:5BTU/h Nota: ● La misura in Watt indica il consumo tipico del dispositivo senza carico esterno. ● La misura in BTU/h indica il consumo di energia del dispositivo a pieno carico.
Ambiente	
Temperatura di esercizio	0-50°C
Temperatura di conservazione	-20 - 60°C
Umidità	0 - 80% di umidità relativa, senza condensa
Proprietà fisiche	
Struttura	Plastica
Peso	0.14 kg (0.31 lb)
Dimensioni (L x P x A)	8.76 x 11.46 x 3.33 cm (3.45 x 4.51 x 1.31 in.)
Lotto scatola	20 pezzi
Nota	Per alcuni prodotti per il montaggio su rack, le dimensioni fisiche standard LxPxA sono indicate utilizzando il formato LxLxA.

Diagramma topologia**ATEN International Co., Ltd.**

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan

Phone: 886-2-8692-6789 Fax: 886-2-8692-6767

www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.
ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
All rights reserved. All other trademarks are the property of their
respective owners.