

2L-2410

Cavo VGA da 10 M



Il cavo VGA è studiato per offrire una connessione VGA di qualità elevata, ideale per applicazioni in alta risoluzione fino a 1920 x 1200. Questo cavo video VGA creato per essere durevole elimina l'effetto ghosting e confuso delle immagini garantendo agli utenti eccezionali esperienze A/V.

Caratteristiche

- Ottimizzato per la trasmissione di segnali analogici
 - Cavo VGA con ingresso femmina e uscita maschio a 15-pin
 - Raggio di piegatura: 90°*
 - Materiale schermato esterno: Nastro Al Mylar
 - Conforme RoHS
 - Compatibile con i prodotti ATEN VGA
- Nota:* 1000 oscillazioni con angolo compreso tra +/- 90 gradi, a una frequenza di 30 volte al minuto

Specifiche

A interfaccia PC/origine	
VGA	HDB-15 maschio
A interfaccia switch	
Porta KVM	HDB-15 femmina

ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan
 Phone: 886-2-8692-6789 Fax: 886-2-8692-6767
 www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.
 ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
 All rights reserved. All other trademarks are the property of their respective owners.