


BC36V9AH

Batteria interna per OL1500LV / OL1500HV



Il pacco batteria interno UPS ATEN è dotato di un design hot-swap, che consente un funzionamento ininterrotto durante la sostituzione della batteria ai sistemi UPS ATEN. Assicura un'alimentazione stabile e offre un'installazione facile, offrendo agli utenti una gestione senza problemi per le loro apparecchiature elettriche.

Nota: Quando il pacco batteria non è in uso, ricaricarlo per 4-6 ore ogni 3-6 mesi.



Specifiche

Elettrico	
Tensione nominale di uscita	36 V
Batteria	
Tipo batteria	Piombo-acido sigillato
Dimensione batteria	9 Ah
Quantità batteria	3
Proprietà fisiche	
Dimensioni (L x P x A)	25.77 x 21.37 x 6.66 cm (10.15 x 8.41 x 2.62 in.)
Peso	8.10 kg (17.84 lb)
Colore	Nero
Ambiente	
Temperatura (di esercizio / immagazzinamento)	Funzionamento: 32 – 104 °F (0 – 40 °C) Stoccaggio: -15 – 45 °C
Umidità (di esercizio e immagazzinamento)	0–95%
Elevazione	Funzionamento: 0-10.000 ft (0-3.000 m) Stoccaggio: 0-50.000 ft (0-15.000 m)
Nota	

ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan Phone: 886-2-8692-6789 Fax: 886-2-8692-6767

www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.
ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
All rights reserved. All other trademarks are the property of their respective owners.