

CS62U

Switch KVM USB VGA/Audio cablato 2-porte (1,8 m)



CS62U 2-Port USB KVM Switch has a handy design integrating with 1.8m of cables. It can control 2 servers via a single console.



Caratteristiche

- One USB console controls two USB computers
- Compact design, built-in 1.8 m cables
- Hotkey selection for OS and keyboard language
- [Computer Selection via hotkey and USB mouse](#) **NEW!**
- Multiplatform support - Windows, Linux, Mac, Sun
- [Video DynaSync™](#) - exclusive ATEN technology eliminates boot-up display problems and optimizes resolution when switching between ports
- [Console mouse port emulation/bypass feature supports most mouse driver](#) **NEW!**
- [USB mouse port can be used for USB hub and USB peripheral sharing](#) *
- [Supports gaming keyboards](#) **NEW!**
- [Supports multifunction and wireless keyboards and mice](#) **NEW!**
- All-in-one design
- With speaker support
- Superior video quality – up to 2048 x 1536; DDC2B
- Auto Scan function to monitor computer operation
- Non-powered
- Sun/Mac keyboard support and emulation*

* 1. PC keyboard combinations emulate Sun/Mac keyboards

2. Sun/Mac keyboards only work with their own computers

Specifiche

Collegamenti del computer	2
Seleziona porta	Tasto di scelta rapida, Mouse
Connettori	
Porte console	1 x HDB-15 femmina (blu) 2 x USB di tipo A femmina 1 x Connettore audio da 3,5 mm femmina (verde)
Porte KVM	2 x HDB-15 maschio (blu) 2 x USB di tipo A maschio 2 x Connettore audio da 3,5 mm maschio (verde)
LED	
Selezionato	2 (verde)
Lunghezza del cavo	
Computer	1,8 m
Emulazione	
Tastiera / Mouse	USB
Video	2048 x 1536 a 60Hz; DDC2B
Intervallo di scansione	5 secondi
Consumo	DC5V:0328W:6BTU
Ambiente	
Temperatura di esercizio	0 - 50 °C
Temperatura di conservazione	-20 - 60 °C
Umidità	0 - 80% di umidità relativa, senza condensa
Proprietà fisiche	
Struttura	Plastica
Peso	0.37 kg (0.81 lb)
Dimensioni (L x P x A)	8.75 x 6.08 x 2.80 cm (3.44 x 2.39 x 1.1 in.)
Nota	Per alcuni prodotti per il montaggio su rack, le dimensioni fisiche standard LxPxA sono indicate utilizzando il formato LxLxA.

Diagramma topologia



ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan
Phone: 886-2-8692-6789 Fax: 886-2-8692-6767
www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.
ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
All rights reserved. All other trademarks are the property of their respective owners.