

IC-428PI

RS-422/485 8 Port PCI card with Isolation / surge protection

특장점

- Fully compliant with PCI Spec. Ver2.2 standard.
- Supports both 64-bit & 32-bit PCI Bus and 3.3V & 5V connector keys.
- High speed serial ports support baud rates up to 921.6Kbps.
- High-tech 128K FIFO can reduce CPU loading, interrupting and improving system performance dramatically.
- Auto Identify and Switch RS-422/485 technology makes user more easy and convenient to manage device without jumpers or switches setting.
- ARSCTM (Auto RTS Signal Control) technology can identify the status of data transceiver or receiver and send RTS signal automatically, instead of using software to control the transmitter.
- Optical isolation (2.5KV) can prevent lightning or high potential voltage damage.
- The embedded surge protection (600W) for all signals are available in this series.
- High speed 16C650 compatible communication controller
- Plug and Play, I/O address and IRQ assigned by BIOS.
- OS Support: Windows 2000, Windows XP

ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan
Phone: 886-2-8692-6789 Fax: 886-2-8692-6767
www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.
ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
All rights reserved. All other trademarks are the property of their respective owners.