

KN2116

16-Port KVM Over the NET™



The KN2116 KVM Over the NET Switch series offers a practical and affordable management solution for data centers housing a large number of servers. These switches are ideal for network administrators who are responsible for mission critical operations and require 24H/7D server room access. The KN2116 allow 3 administrators- one logged in at a local console; the other two logged in remotely from any IP connected web browser-and up to 32 users to securely monitor, manage, troubleshoot or run applications from up to 16 connected devices respectively.

특장점

- 16 port remote access KVM switch monitor and control up to 16 computers from a single KVM (Keyboard, Video, Mouse) console
- Remotely access computers via LAN, WAN, or the Internet; control your installation when and where you want
- · Supports 3 bus sessions 1 Local and 2 Remote administrators can simultaneously access separate ports
- · Internet browser access; Windows client and Java client provided; Java client works with most operating systems
- Graphical OSD and graphical toolbars for convenient, user friendly operation
- Supports all major server platforms and VT100 based serial devices
- Supports multiplatform server environments including PS/2, USB, Sun, and Serial
- RJ-45 connectors allow a full 16 port implementation Cat 5e/6 cable reduces cable bulk
- Cascadable up to 2 levels* provides up to 128/256 computers
- Up to 64 user accounts up to 32 concurrent logins
- Panel Array Mode view all 16 ports at the same time
- Message board feature allows logged in users to communicate with each other and allows a user to take exclusive control of the KVM functions
- Windows based Log Server
- Remote power control for attached Power Over the NET™ devices
- Three level security: multiadministrator; multiuser; multiviewer
- Advanced security features include password protection and advanced encryption technologies 1024 bit RSA; 56 bit DES; 256 bit AES; and 128 bit SSL
- · RADIUS server support
- Flash upgradeable firmware over the network connection
- Ports can be set to Exclusive, Occupy and Share
- Network Interfaces: TCP/IP, HTTP, HTTPS, UDP, RADIUS, DHCP, SSL, ARP, DNS, 10Base-T/100Base-TX, auto sense, Ping
- Detachable front panel for easy access to front and rear of unit
- High video resolution: up to 1280 x 1024 @ 60Hz
- Multiplatform support: Windows 2000/XP, Mac, Linux, Unix, Sun.
- For more information about KVMs which can connect to KN2116, see Compatible KVM Table

^{*} Compatible KVM Switches: KH98, CS9134, CS9138, CS88A, KH1508, KH1516. Some KVM Over the NET™ features may not be supported, depending on the functionality of the cascaded KVM switch.



에이텐 코리아 ATEN KOREA

서울시 금천구 디지털로9길 32(가산동) 갑을그레이트밸리 B동 303호

Tel: 02-467-6789 Fax: 02-467-9876

www.aten.com/kr/ko E-mail: marketing@aten.co.kr



© Copyright 2025 ATEN* International Co. Ltd.
ATEN and the ATEN logo are registered trademarks of ATEN International Co., Ltd.
All rights reserved. All other trademarks are the property of their respective owners.