

KN9108

8-Port KVM Over the NET™



The KN9108 allows two administrators - one logged in at a local console; the other logged in remotely from any IP connected web browser and up to 32 users to securely monitor, manage, troubleshoot or run applications from up to 8 connected devices respectively.

특장점

- 8 port remote access KVM switch itor and control up to 8 computers from a single KVM (Keyboard, Video, Mouse) console
- · Remotely access computers via LAN, WAN, or the Internet ntrol your installation when and where you want
- · Dual-bus: one local and one remote administrator can simultaneously control separate ports
- · Internet browser access, Windows Client and Java Client provided; Java Client works with most operating systems
- · Graphical OSD and graphical toolbars for convenient, user-friendly operation
- Cascadable up to 2 levels* provides up to 64 computers
- Up to 64 user accounts up to 32 concurrent logins
- Panel Array Mode view all 8 ports at the same time
- Message board feature allows logged in users to communicate with each other and allows a user to take exclusive control of the KVM functions
 Windows-based Log Server
- Remote power control for attached Power over the Net[™] devices
- Three level security: multiadministrator; multiuser; multiviewer
- Advanced security features include password protection and advanced encryption technologies 1024 bit RSA, 256 bit AES, 56 bit DES, and 128
 bit SSL
- Remote authentication support: RADIUS, LDAP, LDAPS, and MS Active Directory
- Flash upgradable firmware over network connection
- Ports can be set to Exclusive, Occupy and Share
- Network Interfaces: TCP/IP, HTTP, HTTPS, UDP, RADIUS, DHCP, SSL, ARP, DNS, 10Base-T/100Base-TX, auto sense, Ping
- Detachable front panel for easy access to front and rear of unit
- High video resolution: up to 1280 x 1024 @ 75Hz; 1600 x 1200 @ 60Hz
- Multiplatform support: Windows 2000/XP/Vista, Linux, Unix.

*For more information about KVMs which can connect to KN9108, see <u>Compatible KVM Table</u>. Some KVM Over the NET[™] features may not be supported, depending on the functionality of the cascaded KVM switch.

* Compatible KVM Switches: <u>KH98</u>, <u>CS9134</u>, <u>CS9138</u>, <u>CS88A</u>, <u>KH1508</u>, <u>KH1516</u>. Some KVM Over the NET[™] features may not be supported, depending on the functionality of the cascaded KVM switch.



다이어그램



에이텐 코리아 ATEN KOREA

서울시 금천구 디지털로9길 32(가산동) 갑을그레이트밸리 B동 303호 Tel: 02-467-6789 Fax: 02-467-9876 www.aten.com/kr/ko E-mail: marketing@aten.co.kr



 $\ensuremath{\textcircled{O}}$ Copyright 2025 ATEN* International Co. Ltd. ATEN and the ATEN logo are registered trademarks of ATEN International Co., Ltd. All rights reserved. All other trademarks are the property of their respective owners.