

## VS132

2-포트 VGA 분배기 월 플레이트 (350MHz)



The VS132 Video Splitter is a boosting device to duplicate the video signal from one source to two outputs, and is ideal for any monitor using analog signals. The VS132 also extends the transmission distance up to 65 m (210 feet) making it excellent for public broadcast systems.

To transmit multiple, high quality, VGA, SVGA, XGA, UXGA, QXGA, WUXGA and multisync video signals over long distances without hassle, the VS132 is your best choice. Other useful applications for the VS132 Video Splitter include:

- Financial – the remote display of stock market information
- Education – the remote display of lectures and lessons to lecture halls and classrooms
- Business – the remote display of addresses to overflow rooms; video conferencing; and demos



### 특장점

- One video input to two video outputs
  - Cascadable to three levels – provides up to 8 video signals
  - Supports up to 350 MHz bandwidth
  - Long Distance Transmission – up to 65 m (210 ft)
  - Superior video quality – 1920 x 1440
  - DDC, DDC2, DDC2B Compatible (Port 1 only\*)
  - Supports VGA, SVGA, XGA, UXGA, QXGA, WUXGA and multisync monitors
- Note: If you connect a DDC type monitor to Video Out 1, all other monitors must be able to support the highest video resolution that the DDC monitor can provide.

## 사양

|                |   |
|----------------|---|
| 비디오 입력         |   |
| 인터페이스          | 1 x HDB-15 Male (Blue)                                |
| 적용             | 75 Ω  |
| 최대 거리          | 1.8 m   |
| 비디오 출력         |   |
| 인터페이스          | 2 x HDB-15 Female (Blue)                              |
| 적용             | 75 Ω  |
| 비디오            |   |
| 최대 대역폭         | 350 MHz   |
| 최대 해상도         | Up to 1920 x 1440                                     |
| 최대 거리          | Up to 65 m  |
| 커넥터            |   |
| 전원             | 1 x DC Jack   |
| 사용 환경          |   |
| 사용 온도          | 0-50°C  |
| 보관 온도          | -20 - 60°C  |
| 습도             | 0 - 80% RH, Non-Condensing                            |
| 제품 외관          |   |
| 재질             | Metal   |
| 무게             | 0.19 kg ( 0.42 lb )                                   |
| 크기 (L X W X H) | 10.36 x 7.90 x 2.82 cm<br>(4.08 x 3.11 x 1.11 in.)    |
| 노트             | 일부 랙 마운트 제품은, WxDxH의 표준 물리적 치수를 LxWxH 형식으로 사용하고 있습니다. |

다이어그램



**ATEN International Co., Ltd.**

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan  
Phone: 886-2-8692-6789 Fax: 886-2-8692-6767  
www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.  
ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.  
All rights reserved. All other trademarks are the property of their respective owners.