

AS248T/R

Printer Network



AS248 allows users to share 8 printers via a maximum of 64 computers through switching (24 by default). It is a helpful device to SMEs.

특장점

- At least 24 PCs can share 8 Centronics printers with the AS248 network by means of 4-wire phone lines.
- Simultaneous printing capability.
- Works in bus/star/tree topologies.
- Data Transfer rate: 22 Kbytes per second.
- Cable distance of up to 366m (1200').
- Easy Installation.
- Selects printers by software code operation.
- No external power required.

사양

Function	AS-248R	AS-248T
커넥터		
입력	2 x 6P4C Jacks	1 x DB-25 Male
출력	1 x Centronics C-36 Male	2 x 6P4C Jacks
소비 전력	DC9V, 0.02W	DC9V, 0.02W
Data Rate	22 Kbytes/ Sec. (Max.)	22 Kbytes/ Sec. (Max.)
I/O 중재	First Come First Served	First Come First Served
프린터 선택	Auto/Manual	Auto/Manual
자동 용지 넘김 선택	Enable / Disable	Enable / Disable
타임아웃 선택	5, 10, 25, 60 Second	5, 10, 25, 60 Second
사용 환경		
사용 온도	0 ~50°C	0 ~50°C
보관 온도	-20 ~ 60°C	-20 ~ 60°C
습도	0~80% RH, Non-condensing	0~80% RH, Non-condensing
제품 외관		
재질	Plastic	Plastic
무게	0.05 kg (0.11 lb)	0.05 kg (0.11 lb)
크기 (L X W X H)	7.60 x 6.20 x 2.68 cm (2.99 x 2.44 x 1.06 in.)	7.60 x 6.20 x 2.68 cm (2.99 x 2.44 x 1.06 in.)
노트	일부 랙 마운트 제품은,WxDxH의 표준 물리적 치수를 LxWxH 형식으로 사용하고 있습니다.	

다이어그램



ATEN International Co., Ltd.

3F, No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan
 Phone: 886-2-8692-6789 Fax: 886-2-8692-6767
 www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.
 ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
 All rights reserved. All other trademarks are the property of their respective owners.