

## 2L-2530

Cable VGA de 30 M



Este cable VGA está diseñado para proporcionar una conexión VGA de alta calidad, ideal para aplicaciones de alta resolución de hasta 1920 x 1200. Este cable de vídeo VGA, con una construcción muy duradera, elimina el efecto de imágenes fantasma y difusas, lo que garantiza a los usuarios experiencias de A/V de la máxima calidad.

### Características

- Optimizado para la transmisión de señal analógica
  - Cable VGA con entrada y salida macho de 15 patillas
  - Radio de flexión: 60°\*
  - Material apantallado exterior: Cinta Al Mylar
  - Compatible con los productos VGA de ATEN
- Nota:\* Oscila 3000 veces en ángulos de +/- 60 grados a una frecuencia de 40 veces por minuto

### Especificaciones

Longitud del cable	30 M
Conductor	
Material	Cobre estañado
Diámetro del conductor	30 AWG
Enfundado	
Material	Funda: PVC Apantallado: AL-Mylar
Conectores	
Vídeo	HDB-15 macho HDB-15 macho



Simply Better Connections

***ATEN International Co., Ltd.***

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan  
Phone: 886-2-8692-6789 Fax: 886-2-8692-6767  
www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.  
ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.  
All rights reserved. All other trademarks are the property of their  
respective owners.