

PCEI-SD-35

35U Standard Rack with Perforated Front and Rear Doors



With more than 30 years of experience in R&D and manufacturing cabinet products, ATEN can tailor exclusive products for its customers based on their needs. Our cabinet products, all of which are extremely popular, have been certified by UL and by CE. All ATEN's rack products are EIA/ECA-310-E compliant. Our high-quality cabinets have multiple patents numbered: M377678, M385174, and M513193.

All ATEN's PCE series standard racks are designed for energy saving and carbon reduction, all of which feature heavy-duty construction, intelligent design, safety, and robustness. ATEN rack solutions are ideal for any kinds of data center builds and their cable management.

Caraterísticas

• Heavy-duty Construction

- The frame of the rack consists of three parts: extruded 6063 T5 aluminum columns, beams and beam-to-column connections that are made of aluminum-alloy (ADC12) with t-shaped brackets. For added robustness, beams and columns are connected to beam-to-column connection by M8 screws
- Static loading capacity up to 1800kg and dynamic loading capacity up to 1000kg
- Certified MIL-STD-167/MIL-STD-810G vibration test (Military Standard)
- Certified GR-63-CORE Zone4 seismic test (Equivalent to earthquake of magnitude eight)
- All ATEN's PCE series rack products are EIA/ECA-310-E compliant
- Adjustable mounting rails are made from cold-rolled steel (SPCC). The materials are triple bent so as to enhance its loading capacity

• Airflow Management

- The components of the structure are designed for ergonomics with high-precision quality and for optimizing airflow management to conserve energy and reduce carbon emissions
- Perforated doors for massive front-to-rear airflow provide a ventilation rate above 66%. (The distance cross the corners of the hexagonal mesh is 2mm, and the length of its side is 5mm.)
- Quick-release side panels offer simple and effortless installation
- Multi-module fan unit (2-fan unit / 4-fan unit/ 6-fan unit) can effectively manage the hot air from operating equipment. These are UL compliant and can help increase electrical safety

• Intelligent Design

- Multi-stage quick-release top and bottom covers allow cables to easily pass through the rack
- U positions are numbered on adjustable mounting rails to help IT experts recognize the position to quickly install equipment
- M16 leveling feet secure the racks in place by adjusting the leveling feet even if the racks are set up in a server room with non-raised floors
- Lifting eye-bolts (M16 thread) at the top of the rack, which can be used to hang and move the rack when an elevator is not available
- The high-strength horizontal support rails can disperse the weight of IT equipment, making the racks robust and safe
- Anti-seismic connection design (such as side baying connectors or top baying connectors) offers safe connections in between racks and in between racks and the building

• Certifications

- UL Certified and CE Certified
- Compatible with the latest specification of EIA/ECA-310-E
- Certified MIL-STD-167/MIL-STD-810G vibration test (Military Standard)
- Certified GR-63-CORE Zone4 seismic test (Equivalent to earthquake of magnitude eight)
- Qualified for a static load test of 1800kg

• Includes

- PCEI-SD-35 standard rack enclosure frame × 1 pc
- Perforated front and rear doors with aluminum frame (with door lock and keys) × 2 pcs
- Removable upper and lower side panels × 2 sets
- Roof and floor panels × 1 set
- Caster × 4 pcs
- Leveling feet × 4 pcs
- M5 Mounting Screw × 50 pcs
- Cage nut × 50 pcs

*For more rack door type available to the rack, please refer to the data sheet.

Especificações

Function	PCEI-357560-19	PCEI-359060-19
Número da peça	YFAB-357560-001	YFAB-359060-001
Propriedades físicas		
Altura do Rack (Espaços U)	35U	35U
Altura interna	1558 mm	1558 mm
Altura total, rodízios incluídos	1734 mm	1734 mm
Altura total, rodízios excluídos	1654 mm	1654 mm
Profundidade total	750 mm	900 mm
Largura total	600 mm	600 mm
Cor	Black / White	Black / White
Estrutura do gabinete	AL 6063T5	AL 6063T5
Trilhos EIA de 19"	SPCC / SPHC	SPCC / SPHC
Painéis do teto e do piso	SPCC / SPHC	SPCC / SPHC
Tipo de porta	Perforated Front Door with Alu. Frame Perforated Rear Door with Alu. Frame	Perforated Front Door with Alu. Frame Perforated Rear Door with Alu. Frame
Tipo de painel lateral	Lockable Side Panels - Split	Lockable Side Panels - Split
Carga de peso (estática)	1800 kg	1800 kg
Carga de peso (dinâmica)	1000 kg	1000 kg

ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan

Phone: 886-2-8692-6789 Fax: 886-2-8692-6767

www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.
 ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
 All rights reserved. All other trademarks are the property of their
 respective owners.