

EA1140

Датчик температуры



For environmental monitoring and management, ATEN provides sensor probes that work in tandem with the Power Distribution Units, which enable you to get readings of temperature. Environmental conditions can be monitored with alarms according to customizable minimum/maximum thresholds set for temperature.

*The Sensor is an optional accessory. You can use the ATEN PDU without environmental sensors. However, if you want to have complete energy management of your data center with the full use of ATEN solutions, a sensor installation is required.

Описание

- Measurement range: 0 – 40 °C
- Measurement accuracy: +/- °C
- Compact design – built in 3 m cable
- High sensitivity
- Easy operation

Спецификация

Разъемы	Разъем RJ-11
Измерение	
Диапазон	0 - 40°C
Точность	+/- 1°C
Напряжение питания	5 В постоянного тока (Макс.)
Потребление тока	5 мА (Макс.); 2 мА (сред.)
Температура и влажность	
Рабочая температура	0 - 55°C
Температура хранения	-20 - 70°C
Влажность	< 95% рт. ст.
Физические свойства	
Корпус	Пластмассовый
Масса	0,06 кг
Длина кабеля	3 м

Топологическая схема



3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan
Phone: 886-2-8692-6789 Fax: 886-2-8692-6767
www.aten.com E-mail: marketing@aten.com

