

2L-2402A

1,8 M VGA-kabel med ljud



VGA-kabeln är designad för att tillhandahålla en högkvalitativ VGA-ljudanslutning, särskilt lämpad för applikationer med hög upplösning upp till 1920 x 1200. Den hållbara kabeln eliminerar bild-ghosting och suddiga bilder och garanterar användaren en driftsäker signalöverföring. VGA-kabeln är kompatibel med KVM-switch från ATEN.

Egenskaper

- Optimerad för överföring av analoga signaler med upplösning upp till 1920 x 1200
- VGA-kabel med honingång med 15 stift och haningång
- Ljud stöds
- Skärmd med aluminiumbaserat Mylar-band för driftsäker signalöverföring
- Uppfyller RoHS
- Testad avseende kompatibilitet med VGA KVM-produkter från ATEN

Specifikation

Kabellängd	1,8 m
Skydd	
Material	AL-Mylar
Mantelförsedd	
Material	PVC (Polyvinylklorid)
Ledare	
Material	Förtent koppar
Ledarens diameter	30 AWG
TO PC/källgränssnitt	
VGA	HDB-15 hane
Mini-stereouttag	Ljudplugg (högtalare)
Gränssnitt TO-switch	
KVM-port	HDB-15 hona
Mini-stereouttag	Ljudplugg (högtalare)

ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan
Phone: 886-2-8692-6789 Fax: 886-2-8692-6767
www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.
ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
All rights reserved. All other trademarks are the property of their respective owners.