

VS0108H

8-Port HDMI Splitter



The VS0108H HDMI Splitter is the perfect solution for anyone who needs to send one source of digital high definition video to eight HDMI displays at the same time. It supports all HDMI-enabled equipment, such as DVD players, satellite set-top boxes and all HDMI displays. The VS0108H HDMI Splitter is HDCP (High Bandwidth Digital Content Protection) compliant, making it effective for use with all HDMI displays in home theater applications, as well as in corporate, educational and commercial settings.




Egenskaper

- Connects one HDMI video source to 8 HDMI displays at the same time
- Cascadable to three levels
- Supports Dolby True HD and DTS HD Master Audio
- Up to 60 Hz refresh rate
- Long distance transmission - 20 m (24 AWG)
- Superior video quality - HDTV resolution of 480p, 720p, 1080i and 1080p (1920x1080); VGA, SVGA, SXGA, UXGA and WUXGA (1920x1200)
- HDMI (Deep Color)
- DDC Compatible
- HDCP 1.1 compatible
- Consumer Electronics Control (CEC) allows interconnected HDMI devices to communicate and respond to one remote control
- Signaling rates up to 2.25 Gbits in support of 1080p display
- Rack Mountable

Specifikation

Videosignal ut	
Max. Avstånd	15 M vid 1920 x 1080 vid 60 (4:4:4)
Videosignal in	
Max. Avstånd	3 M vid 1920 x 1080 vid 60 (4:4:4)
Skärmslutningar	
Direkt	8
Maximal	512 (via cascade)
Kontakter	
Telefon	1 x HDMI typ A, hona (svart)
Skärm	8 x HDMI typ A, hona (svart)
Strömuttag	1 x likströmsuttag
LED	
Effekt	1 (orange)
Ineffekt	1 (grön)
Utgång 1-8	8 (grön)
Video	HDTV upp till 1080p; Dator upp till WUXGA (1920 x 1200)
Strömförbrukning	Likström 5,3 V, 9,5 W Notera: ● Mätningen i Watt anger enhetens typiska strömförbrukning utan extern belastning. ● Mätningen i BTU/h anger enhetens strömförbrukning när den är fullt belastad.
Miljö	
Drifttemperatur	0 - 50 °C
Lagringstemperatur	-20 - 60 °C
Luftfuktighet	0 - 80 % relativ luftfuktighet, icke-kondenserande
Fysiska egenskaper	
Hölje	Metall
Vikt	1,74 kg
Mått (L x B x H)	43,20 x 15,40 x 4,40 cm
Notera	För vissa av rackmonterade produkter, observera att de fysiska standarddimensionerna för WxDxH uttrycks med ett LxWxH-format.

Diagram



ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan
 Phone: 886-2-8692-6789 Fax: 886-2-8692-6767
 www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.
 ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
 All rights reserved. All other trademarks are the property of their
 respective owners.