

CE602

USB DVI Dual Link Cat 5 KVM Extender (1024 x 768@60m)



The CE602 is a DVI Dual Link and USB based KVM Extender with RS-232 serial functionality. It allows access to a computer system from a remote console (USB keyboard, monitor, and mouse). Because it allows access to a computer system from a remote console, the CE602 is perfect for use in any type of installation where you need to place the console where it is conveniently accessible, but you want the system equipment to reside in a safe location – away from the dust and dirt of the factory floor, or the harsh environmental influence of a construction site, for example. This allows users to deploy system equipment over large distances.

The CE602 can support up to 2560 x 1600 (DVI Dual Link) resolution. It uses two Cat 5e cables for HDCP, RS-232, microphone and dual link signals. You can also use just one Cat 5e cable if using single link connections.

Features

- Local and Remote Units connect at distances up to 60 m using Cat 5e cable
- Allows access to a computer or KVM installation from a remote console (up to 60 m)
- Supports DVI-D interface and allows transmission of DVI duallink signals
- [Features ATEN technology that allows A/V transmission over one cat 5e cable](#)
- [The 2nd Cat 5e cable is used for HDCP, RS-232, microphone and dual link signals](#)
- Manual compensation control to adjust signal strength in order to compensate for distance
- RS-232 serial ports – connect to a serial terminal, or serial devices such as touchscreens and barcode scanners (Baud Rate 115200 bps)
- Audio Enabled – supports stereo speakers and microphone
- [Built-in 8KV/15KV ESD protection \(Contact voltage 8KV; Air voltage 15KV\)](#)
- [Supports Wide Screen formats](#)
- [Superior video quality of up to 2560 x 1600 @ 60 Hz \(DVI Dual Link\) at 40 m; 1024 x 768 @ 60 Hz at 60 m – get an excellent, crisp image on your screen over long distance transmissions](#)
- Hot pluggable
- Rack mountable
- Easy to install – no software required – connecting cables to the devices is all it takes
- Firmware upgrade

Specifications

Function	CE602L	CE602R
Connectors		
Console Ports	N/A	2 x USB Type A Female (White) 1 x DVI-D Female (White) 1 x Mini Stereo Jack Female (Green) 1 x Mini Stereo Jack Female (Pink)

KVM Ports	1 x DVI-D Female (White) 1 x Mini Stereo Jack Female (Green) 1 x Mini Stereo Jack Female (Pink) 1 x USB Type B Female (White)	N/A
RS-232	1 x DB-9 Female (Black)	1 x DB-9 Male (Black)
Power	1 x DC Jack	1 x DC Jack
Sub / Main	2 x RJ-45 Female (Black)	2 x RJ-45 Female (Black)
LEDs		
Link	1 (Green)	1 (Green)
Power	1 (Green)	1 (Green)
Switches		
EQ Switch	N/A	1 x 8-position switch
Firmware Upgrade	1 x Slide Switch	N/A
Emulation		
Keyboard / Mouse	USB	USB
Video	2560 x 1600 @ 60Hz (40 m, Dual Link) 1024 x 768 @ 60Hz (60 m)	2560 x 1600 @ 60Hz (40 m, Dual Link) 1024 x 768 @ 60Hz (60 m)
Power Consumption	DC5V:2.68W:13BTU/h Note: ● The measurement in Watts indicates the typical power consumption of the device with no external loading. ● The measurement in BTU/h indicates the power consumption of the device when it is fully loaded.	DC5V:5.02W:28BTU/h Note: ● The measurement in Watts indicates the typical power consumption of the device with no external loading. ● The measurement in BTU/h indicates the power consumption of the device when it is fully loaded.
Environmental		
Operating Temperature	0–50°C	0–50°C
Storage Temperature	-20–60°C	-20–60°C
Humidity	0–80% RH, Non-condensing	0–80% RH, Non-condensing
Physical Properties		
Housing	Metal	Metal
Weight	0.48 kg (1.06 lb)	0.48 kg (1.06 lb)
Dimensions (L x W x H)	20.20 x 8.54 x 2.50 cm (7.95 x 3.36 x 0.98 in.)	20.20 x 8.68 x 2.50 cm (7.95 x 3.42 x 0.98 in.)
Note	For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.	

Diagram

