

## PE0212

Basic PDU Series

PE0212A



The PE0212 series Basic PDU contains 12 AC outlets and is available in IEC or NEMA socket configurations. The PE0212 series Basic PDU features a space-saving 1U design that allows it to be mounted vertically on the outside of a rack, resulting in a more efficient use of space in the server room, while providing 12 AC outlets.

### Features

- **Basic PDU**
  - Space saving -1U rack mount design
  - IEC or NEMA outlet models
  - Aluminum material

- **Typical Applications**

- Servers
- Network Devices
- Telecom Equipment

### Specifications

Function	PE0212A	PE0212B	PE0212G
Electrical			
Nominal Input Voltage	100-120 VAC	100-240 VAC	100-240 VAC
Maximum Input Current	20A Max (UL de-rated 16A Max)	20A (Max) (UL de-rated 16A Max)	16A (Max)
Input Frequency	50-60 Hz	50-60 Hz	50-60 Hz
Input Connection	For A Plug NEMA L5-20P For A2 Plug : NEMA 5-20P	NEMA L6-20P	IEC-320 C20

Input Power	2400VA(MAX) ; 1920VA(UL de-rated)	4800VA(Max); 3840VA(UL de-rated)	3840VA(Max)
Outlet Type	(12) NEMA 5-20R	(12) IEC 320 C13	(12) IEC 320 C13
Maximum Output Current (Outlet)	20A (Max) (UL de-rated 16A Max)	15A (Max) (UL de-rated 12A Max)	10A (Max)
Maximum Output Current (Bank)	20A (Max) (UL de-rated 16A Max)	20A (Max) (UL de-rated 16A Max)	16A (Max)
Maximum Output Current (Total)	20A (Max) (UL de-rated 16A Max)	20A (Max) (UL de-rated 16A Max)	16A (Max)
OPD(Overcurrent Protection Device)	Yes	Yes	Yes
Physical Properties			
Dimensions (L x W x H)	48.20 x 4.44 x 4.50 cm (18.98 x 1.75 x 1.77 in.)	48.20 x 4.44 x 4.50 cm (18.98 x 1.75 x 1.77 in.)	48.20 x 4.44 x 4.50 cm (18.98 x 1.75 x 1.77 in.)
Weight	0.67 kg ( 1.48 lb )	0.67 kg ( 1.48 lb )	0.67 kg ( 1.48 lb )
Power Cord Length	10ft(12#)	10ft(12#)	10ft(3x1.5mm2)
Environmental			
Temperature (Operating / Storage)	0 – 40°C / -20 – 60°C *When the environmental temperature comes close 40 degrees, it is recommended to lower the load to 60% to comply to the safety regulations.	0 – 40°C / -20 – 60°C *When the environmental temperature comes close 40 degrees, it is recommended to lower the load to 60% to comply to the safety regulations.	0 – 40°C / -20 – 60°C *When the environmental temperature comes close 40 degrees, it is recommended to lower the load to 60% to comply to the safety regulations.
Elevation (Operating / Storage)	3000m	3000m	3000m
Compliance			
EMC Verification	FCC Class A	FCC Class A	-
Safety Verification	UL, other by request	UL, other by request	LVD,UL
Note	For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.		

**Diagram****ATEN International Co., Ltd.**

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan

Phone: 886-2-8692-6789 Fax: 886-2-8692-6767

www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.  
ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.  
All rights reserved. All other trademarks are the property of their  
respective owners.