
2L-7D02DP

2 m DisplayPort rev.1.4 Cable



The ATEN DisplayPort rev.1.4 Cable supports 32.4 Gbps data rate with high-definition connectivity and advanced auxiliary channeling. It is a professional connection of your DisplayPort supported (gaming) PC, use in conjunction with ATEN DisplayPort solutions, laptop to an ultra high resolution monitor, or other DisplayPort interface devices. Our DisplayPort rev.1.4 Cable allows for up to 8K Dynamic HDR with 32 channels for high quality video and audio experience. Each connector features latches that provide a secure connection with a release button.



Features

- Crystal-clear video up to 8K (7680 x 4320 @ 60Hz), backward compatible with 5K (5120 x 2880 @ 60Hz) and 4K (4096 x 2160 @ 120Hz) and previous generations of DP
- High Bit Rate 3 (HBR3) bandwidth of 32.4 Gbps
- Multi-Stream Transport (MST) for daisy-chaining multiple monitors
- Forward Error Correction
- Display Stream Compression (DSC)
- 32 uncompressed digital audio channels
- RoHS compliant

Specification

| | |
|-----------------------|-----------------------------------|
| Max. Video Resolution | 7680x4320@60Hz |
| Physical Properties | |
| Cable Length | 2M |
| Cable Color | Black |
| Cable Outer Dimension | 6.5 ± 0.2mm |
| Conductor Gauge | 30AWG |
| Conductor Material | Tinned Copper |
| Connector Plating | Nickel |
| Connector Type | DisplayPort (20 pin) Male to Male |
| Cable Shield Type | Aluminum Magnesium Alloy |
| Cable Jacket Type | PVC |
| Environmental | |
| Operating Temperature | 80°C |
| Rating | UL VW-1 (Flame rate), CSA |