

2L-2403

3M VGA Cable



The VGA Cable is designed to provide a high quality VGA connection, ideally suited for high resolution applications up to 1920 x 1200. This durably constructed VGA video cable eliminates the picture ghosting and fuzzy images, guaranteeing users the ultimate A/V experiences.

Features

- Optimized for analog signal transmission
- VGA cable with 15-pin female input and male output
 Bend Radius: 90°*
- Outer shielded material: Al Mylar tape
- · RoHS compliant
- Compatible with ATEN VGA products Note:* Swings 1000 times between angles of +/- 90 degrees, at a frequency of 30 times per minute

Specification

| Conductor | |
|--------------------|------------------------------------|
| Material | Tinned Copper |
| Conductor Diameter | 30 AWG |
| Jacketed | |
| Material | Jacket: PVC Shielding: AL-Mylar |
| Connectors | |
| Video | HDB-15 Male HDB-15 Female |
| Cable Length | 3 m |



ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan Phone: 886-2-8692-6789 Fax: 886-2-8692-6767

www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.
ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
All rights reserved. All other trademarks are the property of their respective owners.