

## 2L-5203B

3M Port Switching VGA Cable



The VGA Cable is designed to provide a high quality VGA connection, ideally suited for high resolution applications up to 1920 x 1200. Featuring durable design, the cable eliminates the picture ghosting and fuzzy images, guaranteeing users a reliable signal transmission. For application utility, the VGA cable is compatible with ATEN KVM switches to change KVM port focus.

### Features

- Optimized for analog signal transmission at resolution up to 1920 x 1200
- VGA cable with 15-pin female input and male output
- Audio supported
- Outer shielded with Al Mylar tape for reliable signal transmission
- RoHS compliant
- Tested for compatibility with ATEN VGA KVM products

**Specification**

Cable Length	3m
Switches	
Port Selection	Port Switching Button
Shield	
Material	AL-Mylar
Jacketed	
Material	PVC (PolyVinyl Chloride)
Conductor	
Conductor Diameter	30 AWG
Material	Tinned copper
TO Switch Interface	
KVM Port	HDB-15 Female
Mini Stereo Jack	Audio Plug (Speaker)
TO PC/Source Interface	
VGA	HDB-15 Male
Mini Stereo Jack	Audio Plug (Speaker)

**ATEN International Co., Ltd.**

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan  
 Phone: 886-2-8692-6789 Fax: 886-2-8692-6767  
 www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.  
 ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.  
 All rights reserved. All other trademarks are the property of their  
 respective owners.