

CS64U

4-Port USB VGA/Audio Cable KVM Switch (1.8m)



The CS64U takes a giant step forward from prior cable KVM models, by offering built-in cables, USB peripheral sharing, and a firmware upgrade function that allows you to keep up with latest available versions.

Furthermore, the CS64U features enhanced Video DynaSync™ technology, which stores the console monitor's EDID (Extended Display Identification Data) to optimize display resolution. The CS64U also offers multiplatform support and computer selection via hotkeys to provide the ultimate in desktop convenience.

Features


- One USB console controls four USB computers
- Compact design, built-in 1.8 m cables
- Hotkey selection for OS and keyboard language
- Computer Selection via hotkey
- Multiplatform support - Windows, Linux, Mac, and Sun
- Video DynaSync™ - exclusive ATEN technology eliminates boot-up display problems and optimizes resolution when switching between ports
- USB mouse port can be used for USB 1.1 hub and USB 1.1 peripheral sharing
- Supports multifunction and wireless keyboards and mice
- All-in-one design
- With speaker support
- Superior video quality – up to 2048 x 1536 @ 60 Hz ; DDC2B
- Auto Scan function to monitor computer operation
- Bus-powered
- Sun/Mac keyboard support and emulation*
- Firmware upgradable

- * 1. PC keyboard combinations emulate Sun/Mac keyboards
2. Sun/Mac keyboards only work with their own computers

Specification

Computer Connections	4
Port Selection	Hotkey
Connectors	
Console Ports	1 x HDB-15 Female (Blue) 2 x USB Type A Female 1 x 3.5mm Audio Jack Female (Green)
KVM Ports	4 x HDB-15 Male (Blue) 4 x USB Type A Male 4 x 3.5mm Audio Jack Male (Green)
LEDs	
Selected	4 (Green)
Cable Length	
Computer	4 x 1.8 m
Emulation	
Keyboard / Mouse	USB
Video	2048 x 1536 @ 60Hz; DDC2B
Scan Interval	1-99 seconds
Power Consumption	DC5V:0.9W:8BTU/h Note: ● The measurement in Watts indicates the typical power consumption of the device with no external loading. ● The measurement in BTU/h indicates the power consumption of the device when it is fully loaded.
Environmental	
Operating Temperature	0 – 50°C
Storage Temperature	-20 – 60°C
Humidity	0 – 80% RH, Non-condensing
Physical Properties	
Housing	Plastic
Weight	0.73 kg (1.61 lb)
Dimensions (L x W x H)	9.41 x 9.72 x 2.60 cm (3.7 x 3.83 x 1.02 in.)
Note	For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.

Diagram



ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan
 Phone: 886-2-8692-6789 Fax: 886-2-8692-6767
 www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.
 ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
 All rights reserved. All other trademarks are the property of their
 respective owners.