

CS82A

2-Port PS/2 VGA KVM Switch



CS82A is a KVM switch with built-in PS/2 on each of the front and rear panels. It can control 2 servers via a single console and allows users to switch between computers via the buttons on the front panel of the switch or the hotkey configuration on the keyboard. It is the simplest and most convenient solution for multi-computer management. The sturdy, durable and small enclosure design is its important feature.



Features

- One PS/2 console controls 2 computers.
- Computer selection via front panel pushbuttons and hotkeys.
- Superior video quality- up to 1920 x 1440; DDC2B.
- Supports Microsoft IntelliMouse, Logitech MouseMan, FirstMouse and IBM Scrollpoint Mouse.
- Compact, Sturdy, Durable Metal Housing.
- Keyboard and mouse emulation for error free booting.
- Auto Scan function to monitor computer operation.
- Non-powered.
- OS Compatibility: DOS, WIN 98, WIN ME, WIN NT, WIN 2K, WIN XP, WIN 2003, [Windows Vista](#), LINUX, Mac 8.6/9/10 and SUN Solaris 8/9 (with optional adapter).

Specification

2-Port PS/2 KVM Switch

| | |
|----------------------|---|
| Computer Connections | 2 |
| Port Selection | Hotkey, Pushbutton |
| Connectors | |
| Console Ports | 1 x HDB-15 Female (Blue) 1 x 6-pin Mini-DIN Female (Purple) 1 x 6-pin Mini-DIN Female (Green) |

| | |
|------------------------|---|
| KVM Ports | 2 x HDB-15 Male (Blue) 2 x 6-pin Mini-DIN Female (Purple) 2 x 6-pin Mini-DIN Female (Green) |
| Power | 1 x DC Jack |
| Switches | |
| Ports | 2 x Pushbutton |
| LEDs | |
| Online | 2 (Orange) |
| Selected | 2 (Green) |
| Emulation | |
| Keyboard / Mouse | PS/2 |
| Video | 1920 x 1440 @ 60Hz; DDC2B |
| Scan Interval | 3, 5, 10, 20 Seconds |
| Power Consumption | DC9V:0.3W:6BTU |
| Environmental | |
| Operating Temperature | 0°~50°C |
| Storage Temperature | -20°~60°C |
| Humidity | 0~80% RH, Non-condensing |
| Physical Properties | |
| Housing | Metal |
| Weight | 0.54 kg (1.19 lb) |
| Dimensions (L x W x H) | 14.00 x 8.80 x 5.55 cm (5.51 x 3.46 x 2.19 in.) |
| Note | For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format. |

Diagram



ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan
Phone: 886-2-8692-6789 Fax: 886-2-8692-6767
www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.
ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
All rights reserved. All other trademarks are the property of their respective owners.