

KA9570

USB KVM Adapter Cable (CPU Module)



The Altusen USB CPU adapters connect KVM cables to the USB console ports of the servers. Those adapters are light and in small form factor, fit perfectly into most of the rack-mount or desktop servers.

Features

- Auto Signal Compensation (ASC), no DIP switch setting needed for the different distances.
- Hot pluggable - add or remove computers without having to power down the switch.
- Lifetime firmware upgrades.
- Superior video quality - supports resolution of up to 1280 x 1024 within the distance of up to 40m (130'); DDC2B.
- Built in ASIC for greater reliability and compatibility.
- CPU module designed with automatic conversion to allow for flexible interface combinations (PS/2, USB) to control all computer types (PC, Mac).
- Compact size

Note: Not Compatible with Matrix KVM Switch [KM0832/KM0432/KM0216](#).

Specification

| | |
|------------------------|---|
| Connectors | |
| Link | 1 x RJ-45 Female |
| Computers | 1 x USB Type A Male 1 x HDB-15 Male |
| LEDs | |
| Online | 1 (Green) |
| Link | 1 (Orange) |
| Physical Properties | |
| Housing | Plastic |
| Weight | 0.15 kg (0.33 lb) |
| Dimensions (L x W x H) | 9.00 x 4.30 x 2.18 cm (3.54 x 1.69 x 0.86 in.) |
| Note | For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format. |

Diagram



ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan
 Phone: 886-2-8692-6789 Fax: 886-2-8692-6767
 www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.
 ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
 All rights reserved. All other trademarks are the property of their
 respective owners.