

CLCS1716iKIT

CL1000M(LCD Console) with CS1716i(16-Port IP KVM) Bundle



ATEN's 17" LCD integrated console and 16-port IP KVM bundle offers a streamlined and economic approach to IT environments. The [CL1000M](#), incorporates a keyboard with touchpad and a 17" LCD monitor into a 1U Slideaway housing.

The bundled ATEN IP KVM, [CS1716i](#), allows you to manage 8 computers either directly from the [CL1000M](#), or remotely from anywhere on your network or the internet.

[CL1000M](#) 17" LCD Integrated Console

[CS1716i](#) 16-port IP KVM Switch

Features

- **Hardware**
- 16-port remote access KVM switch - monitor and control up to 16 computers from a single KVM console
- Daisy chain up to 15 additional units - control up to 256 computers
- Auto-sensing of station's position on daisy chained installations; no need for manual dip switch setting; front panel LED indicates station's position
- Multiplatform support - Windows, Linux, Mac, and Sun
- Dual Interface - supports PS/2 or USB keyboard and mouse computers
- Video DynaSync™ - stores the console monitor's EDID (Extended Display Identification Data) to optimize display resolution
- Superior video quality - up to 2048 x 1536; DDC2B for the local console; up to 1600 x 1200 @ 60Hz / 24 bit color depth for remote sessions
- BIOS-level access
- Mouse DynaSync
- Rack mountable in a 19" system rack
-


Management

- Panel array mode enables user to monitor multiple servers from single screen at the same time - each selected server's video output appears in a separate panel - users can easily select the number of panels to view
- Event Logging
- Up to 32 concurrent logins
- Broadcast mode; operations simultaneously performed on all selected computers (software installation, system-wide shutdown, etc.)
- Port names automatically reconfigured when station sequence is changed
- Message board allows logged in users to communicate with each other, and allows a user to take exclusive control of the KVM functions
- On-screen keyboard with multilanguage support
-

Security

- Secure keyboard/mouse/video transmission via RC4 128bit encryption
- 128bit SSL browser access
- Two level password security - up to 64 user accounts with separate profiles for each
- External(remote) authentication support: RADIUS, LDAP, LDAPS, MS Active Directory
- Support for IP/Mac Filter
- Local and remote access logged and authenticated

Diagram



ATEN International Co., Ltd.

3F, No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan
 Phone: 886-2-8692-6789 Fax: 886-2-8692-6767
 www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.
 ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
 All rights reserved. All other trademarks are the property of their respective owners.