

---

## CS1208DL / 1216DL

8/16-Port Slideaway LCD KVM Switch



The power supply of [CS1208DL/CS1216DL](#) supports DC-36V-72V. To industries using specific racks, such as the data communication industry, this function fulfills the power supply needs of the rack from KVM Switches.

20050912132331001.jpg

### Features

- Daisy chain up to 31 additional CS-1216A series unit - control up to 512 computers from the unit's Slideaway console.
  - Neat high-quality cable for the high-density server rack.
  - No software required - convenient computer selection via intuitive hotkey combination or On Screen Display (OSD) menu- OSD port list automatically expands when stations are added.
  - Security - administrator / user password authorization for enhanced security protection (PSP), administrator synchronized confirmation between first and chained stations.
  - Two types of logout :manual and timed.
  - Detachable modular KVM switch for easy maintenance.
  - DDC emulation VGA setting of every connected computer are automatically adjusted for optimal output to the LCD monitor.
  - Supports special DC -36V to -72V power supply.
  - Drawer access lock - an easy to use feature that enables the Slideaway's console drawer to remain securely locked away in position when not in use.
  - Rack mountable in a 19" (1U) system rack with a depth of up to 36 inches.
  - Buzzer ON/OFF via hotkey and OSD.
  - Broadcast Mode: Operations simultaneously performed on all selected computers, software installation and upgrading, system wide shutdown....etc.
  - A-Grade TFT LCD Panel.
  - Multiplatform support:DOS, Windows 2003/ 2000/XP/98/ME/NT and Linux.
-