



## VK108US

ATEN Control System - 8-button Keypad (US, 1 Gang)



The VK108US is a fully-customizable 8-button keypad designed for use with the ATEN Control System. The keypad provides an interface to control devices in a room from a standard wall mounted faceplate. Created with flexibility in mind, the one-gang keypad can be laid out in 14 different combinations of 4 to 8 buttons that snap together as easy as Lego's. By connecting to the [VK2100/VK1100](#) Control Box over a LAN, users will find it's effortless using [VK6000](#) software to configure the desired control of any connected device from the keypad. With the button's ready to go, you have instant and smart control of the facilities from a keypad or keypads that can manage any device in the room. The VK108US is an affordable solution, perfect to serve as the primary interface in small meeting rooms, or as secondary device control in classrooms and conference centers.

### Keypad Layout Example



Custom button placement on the keypad can be set in 14 different combinations of 4 to 8 buttons. The example above shows the 10 most commonly used.




## Features

- Key pad - provides physical connection to the ATEN Control System
- Fully customizable with 14 layout combinations of 4 to 8 buttons
- System LED indicators for quick connection status check
- Dual-color button LEDs for clear indication and visibility in dark environments
- Easy ID pairing with Control Box for Ethernet communication
- Up to 8 keypads connect to a single Control Box for future scalability
- Unrestricted modes support flexible behavior settings for each button
- Intuitive web GUI for easy keypad configuration
- Dual power supply – DC 5V or Power over Ethernet
- [Customized button engraving service](#)

## Specification

Interfaces	
Ethernet	<ul style="list-style-type: none"> <li>• 1 x RJ-45 Female, 10/100Base-T</li> <li>• Supported Protocol: ARP, ICMP, TCP/IP, DHCP, HTTPS</li> <li>• DHCP-enabled. The following default IP settings will be used if no IP is assigned within 30 seconds: IP: 192.168.0.60 Subnet Mask: 255.255.255.0</li> </ul>
Keypad Layout	4~8 buttons customizable in 14 keypad layouts
Switches	
Controller ID	1 x 16-segment Switch
Keypad ID	1 x 8-segment Switch
Reset Button	1 x Semi-recessed Pushbutton
Power Consumption	DC5V:1.25W:6BTU DC48V:1.58W:7BTU
Environmental	
Operating Temperature	0 – 50°C
Storage Temperature	-20 – 60°C
Humidity	0 - 80% RH, Non-Condensing
Physical Properties	
Housing	Plastic
Weight	0.13 kg ( 0.29 lb )
Dimensions (L x W x H)	11.63 x 7.06 x 3.89 cm (4.58 x 2.78 x 1.53 in.)
Faceplate Dimension (L x W x H)	11.92 x 7.42 x 0.92 cm (4.69 x 2.92 x 0.36 in.)
Note	For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.

Diagram



**ATEN International Co., Ltd.**

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan  
 Phone: 886-2-8692-6789 Fax: 886-2-8692-6767  
 www.aten.com E-mail: marketing@aten.com

© Copyright 2015 ATEN® International Co., Ltd.  
 ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.  
 All rights reserved. All other trademarks are the property of their respective owners.