

VE800

HDMI Extender



The VE800 HDMI Extender extends your HDMI display up to 60 m away from your HDMI source using two Cat 5e cables. It is equipped with HDMI (high definition multimedia interface) connectors and is capable of supporting DVI-D (Single-Link) equipment when used with a HDMI-to-DVI adapter, providing greater flexibility and installation options when integrating several home theater components.



Features

- Extends the distance between HDMI source and HDMI display
- Uses Cat 5e cable to achieve long distance transmission
- 8 segment equalization adjustment switch
- Extend 1080p by 40m; extend 1080i (HDTV) by 60m
- Superior video quality 1920 x 1200, up to 1080p
- HDMI (3D, Deep Color)
- Supports Dolby True HD and DTS HD Master Audio
- DDC compatible
- HDCP 1.1 Compatible
- Compatible with all ATEN HDMI switches and splitters



Specification

Function	VE800L	VE800R
Device Connections	1	N/A
Connectors		
Display	N/A	1 x HDMI Type A Female (Black)
Device	1 x HDMI Type A Female (Black)	N/A
Unit To Unit	2 x RJ-45 Female	2 x RJ-45 Female
Power Jack	1 x DC Jack	1 x DC Jack
LEDs		
Power	1 (Orange)	1 (Orange)
Online	N/A	1 (Green)
Video Resolution	HDTV resolutions: 480p, 720p, 1080i, 1080p(1920 x 1080); PC resolutions: VGA, SVGA, XGA, SXGA, UXGA, WUXGA (1920 x 1200)	HDTV resolutions: 480p, 720p, 1080i, 1080p(1920 x 1080); PC resolutions: VGA, SVGA, XGA, SXGA, UXGA, WUXGA (1920 x 1200)
Power Consumption	DC5V:1.22WBTU/h Note: • The measurement in Watts indicates the typical power consumption of the device with no external loading. • The measurement in BTU/h indicates the power consumption of the device when it is fully loaded.	DC5V:0.95WBTU/h Note: • The measurement in Watts indicates the typical power consumption of the device with no external loading. • The measurement in BTU/h indicates the power consumption of the device when it is fully loaded.
Environmental		
Operating Temperature	0–50°C	0–50°C
Storage Temperature	-20–60°C	-20–60°C
Humidity	0-80% RH, Non-condensing	0 - 80% RH, Non-Condensing
Physical Propert	ies	L
Housing	Metal	Metal
Weight	0.16 kg (0.35 lb)	0.16 kg (0.35 lb)
Dimensions (L x W x H)	9.00 x 5.50 x 2.40 cm (3.54 x 2.17 x 0.94 in.)	9.00 x 5.74 x 2.40 cm (3.54 x 2.26 x 0.94 in.)
Note	For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.	
	1	



Diagram

HDMI Cable	HDMI Cable
VE800L (Right)	VE800R (Right)
VE800L (Left)	VE800R (Left)
TMDS DDC	TMDS DDC EQ
Cat 5e Cable	

ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan Phone: 886-2-8692-6789 Fax: 886-2-8692-6767 www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd. ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd. All rights reserved. All other trademarks are the property of their respective owners.