Simply Better Connections

IC485S

RS-232/RS-485 Interface Converter



IC485S is a 2-way converter for converting RS-232 signals to and from RS-422/RS-485 signals in long-distance applications up to 1200 m (4000 ft.). It supports the connection of up to 32 hubs and features monitoring to confirm the data passing between devices.


Features

- Data transmission controlled by the RTS signal.
- DCE/DTE selectable.
- Point to point, multidrop, and simplex/duplex link selection.
- Four wire full duplex; two wire half duplex.
- Compact size.
- Cable distance of up to 1200m (4000 ft.).
- Monitor configuration support.
- Supports baud rates up to 115.2Kbps.
- OS Support: Windows 2000, Windows XP

Specification

Connectors	1 DB-25 Female (RS-232) RS-485 / RS-422 Four Terminal Block 1x RJ-11 Female
Switches	DCE, DTE, Monitor TxON, RxON TxRTS, RxRTS TxRTS, RxON
Power Consumption	DC9V:0.82W:2BTU
Signal Range	1200 m [4000'] (Max)
Data Rate	Up to 100 Kbps under 1200 m [4000']
Environmental	
Operating Temperature	0 ~50˚C
Storage Temperature	-20 ~ 60˚C
Humidity	0~80% RH, Non-condensing
Physical Properties	
Housing	Plastic
Weight	0.05 kg (0.11 lb)
Dimensions (L x W x H)	7.90 x 5.45 x 2.10 cm (3.11 x 2.15 x 0.83 in.)
Note	For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.

Diagram



ATEN International Co., Ltd.
3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan
Phone: 886-2-8692-6789 Fax: 886-2-8692-6767
www.aten.com E-mail: marketing@aten.com

© Copyright 2015 ATEN® International Co., Ltd.
ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
All rights reserved. All other trademarks are the property of their
respective owners.