
CS102U

2-Port USB VGA KVMP™ Switch



CS102U is a KVM Switch with built-in USB. It can control 2 servers via a single console and allows servers to share 2 peripheral devices via the USB ports on the rear panel. Users can switch between computers via the buttons on the front panel the switch. It is the simplest and most convenient solution for multi-computer management.

Features

- One USB console controls 2 computers
- 2 port USB Hub built in
- Control a Mac and a PC at the same time
- Computer selection via front panel pushbuttons
- Superior video quality - up to 1920 x 1440; DDC2B
- Supports Microsoft IntelliMouse and the scrolling wheel on most mice
- Auto Scan function to monitor computer operation
- Non-powered
- OS Support: Windows 2000, Windows XP, [Windows Vista](#), LINUX, Mac and FreeBSD

Specifications

Computer Connections	2
Port Selection	Pushbutton
Connectors	
Console Ports	2 x USB Type A Female (White) 1 x HDB-15 Female (Blue)
KVM Ports	2 x USB TYPE B Female (White) 2 x HDB-15 Male (Blue)
USB Hub	2 x USB Type A Female (White)
Power	1 x DC Jack (Black)
LEDs	
Online	N/A
Selected	2
Auto Scan	N/A
Video	1920 x 1440; DDC2B
Scan Interval	5 seconds
Power Consumption	DC5V:0.11W:26BTU/h Note: <ul style="list-style-type: none">● The measurement in Watts indicates the typical power consumption of the device with no external loading.● The measurement in BTU/h indicates the power consumption of the device when it is fully loaded.
Environmental	
Operating Temperature	0~50°C
Storage Temperature	-20~60°C
Humidity	0~80% RH, Non-condensing
Physical Properties	
Housing	Plastic / Metal
Weight	0.15 kg (0.33 lb)
Dimensions (L x W x H)	12.00 x 6.52 x 4.40 cm (4.72 x 2.57 x 1.73 in.)
Note	For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.

Diagram

