

KE6910T

2K DVI-D Dual Link KVM over IP Transmitter



The KE6910 2K DVI-D Dual Link KVM over IP Extender consists of a high performance IP-based transmitter (KE6910T) that connects to the computer and receiver (KE6910R) that provides console access from a separate location. The KE6910 allows access to a computer system from a remote USB console (USB keyboard, USB mouse, DVI monitor) over an intranet, enabling users to locate computers in a secure and temperature controlled environment, which is isolated from users' workstation.

The KE6910 supports one DVI display at each end, providing video resolutions up to 2560 x 2048 @ 50Hz and flawless and lossless video compression quality with minimal latency. The extender also supports 2K x 2K video resolution (2048 x 2048 @ 60Hz), which is used widely in the Air Traffic Control (ATC) industry

The KE6910 supports connections via an RJ-45 port or a SFP slot. The transmitter and receiver can be connected either directly to each other or via a high-speed network, over a copper-based or fiber-based LAN, ensuring 24/7 availability of remote access to servers. To connect via the SFP slot, the extender supports 1Gbps SFP fiber module 1 expansions, enabling connections via fiber optic network to extend transmission distances up to 10km. The KE6910 also provides dual power supplies for redundancy

The KE6910 can be set on a desk, mounted on a wall or at the rear of a rack with its space-saving 0U rack-mount design. As an IP-based matrix extender, the KE6910 can be used as a point-topoint / point-to-multipoint / multipoint-to-point extender, or integrated into a KVM over IP Matrix System (multipoint-to-multipoint) when combined with the CCKM, providing more flexible applications in different working environments.

When integrated with the CCKM, the KE6910 supports more advanced features such as authentication lock, connection redundancy, disconnection alert, boundless switching, "Push" and "Pull", video wall and multi-display setups, and profile scheduling that provide uninterrupted access with quick and easy control tools to use the KE6910 over a network.

More functions include auto detection of all KVM over IP extenders 2 in the same subnet for the sake of fast installation or configuration, username / password authentication and authorization, and the ability to define different types of connections that can be switched and shared. Security features also provide extra protection, supporting AES encryption for secured data transmissions, while RADIUS, LDAP, AD or remote user authentication provides an added layer of connection security; moreover, with an OSD, RS-232 support, and Auto MDIX, the KE6910 is the most cost-effective and convenient way to get a full digital extension from anywhere on the intranet

Whether users are monitoring, operating, controlling or extending computer access, the KVM over IP Matrix System is made adaptable, to fit an endless variety of working environments and workstation settings, to provide solutions in traffic management centers, retail surveillance centers, facility situation rooms, command control centers, utilities process control centers, broadcasting distribution monitoring systems, network operations centers (NOC), and many other industries where matrix extending is required.

- 1. The SFP module $(\underline{2A-136G} / \underline{2A-137G})$ is sold separately. Contact your ATEN dealer for product information.
- 2. Refer to www.aten.com for more about the KVM over IP extenders. For the latest list of compatible network switches, please visit: ATEN Support Center for more information.

- Exclusive Features for ATC Industry¹
 - Supports 2K x 2K video resolution (2048 x 2048 @ 60Hz)
 - Boundless Switching simply move the mouse cursor across screen boundaries to switch between different receivers (Rx)
 - Fast Switching switches between different remote video resolutions on a local display within 0.3 seconds
 - "Push" and "Pull" shares content instantly to/from a single Rx or video wall by just one click
 - Authentication Lock automatically logs in when the power of the system is resumed after power off
 Connection Redundancy automatically connects to another transmitter (Tx) after disconnection with the original Tx, ensuring constant access to servers

 - Disconnection Alert Pop-up warning message and looping alarm beeping notify users the disconnection status
 - Supports power / network failover ensures constant availability for mission-critical applications (2 DC jacks for KE6910; 1 RJ-45 and 1 SFP fiber for network failover)

Advanced Features¹

- ATEN Matrix Link allows users instant link transmitters and receivers, and perform real-time port and profile switching on an iPad
- Video Walls creates multiple video walls with up to 12 x 12 (144 displays max.) in each layout
- Flexible connections allows multiple extender and matrix connections for multi-display installations and video wall applications
- On-screen Preview (Panel Array™ Mode) allows users to view the video of up to 36 displays on one screen



- Advanced Scheduling improves efficiency and saves costs by allowing connections to be set based on time and date
 Channel connections allow RX devices to connect to multiple TX devices to streams video, audio, USB and serial sources independently

- Virtual Transmitter independently streams video, audio, USB, and serial sources from different Tx
 Internal and external authentication support supports LDAP, Active Directory, RADIUS and TACACS+ external authentications
 Advanced user authorization settings administrators can set four access modes of permissions on Tx devices for collaboration or to avoid interference among users
- Video grouping of up to 4 sets of KE series devices to support Multi-Display applications
- Configurable user and group permissions for access and control of KVM over IP extenders
- Rx access control users at the Tx local console can enable / disable Rx access by simply pressing a control button ²

Note:

- 1. These advanced functions are supported when the KE transmitters are paired with KE receivers and managed by CCKM.
- 2. The KVM over IP Access Control Box (2XRT-0015G) is sold separately. Contact your ATEN dealer for product information.

Hardware

- Supports 1Gbps SFP fiber module expansions up to 10 km ¹
- Advance processor provides lossless and low latency video transmissions up to 2560 x 1600 @60 Hz and 2560 x 2048 @50 Hz
- Audio enabled supports stereo speakers and microphone
- High speed USB Storage Transmission support Auto-MDIX automatically detects cable type
- Built-in 8KV/15KV ESD protection and 2KV surge protection
- Fanless design for silent operations that are energy efficient
 Rack Mountable Mounting options:
- •2X-021G Dual Rack Mount Kit
- •2X-031G Single Rack Mount Kit
- Includes an industrial-grade power adapter supports operating temperature of 0°C-50°C to ensure durability and adaptability under harsh environmental conditions

1. The SFP module (2A-136G / 2A-137G) is sold separately. Contact your ATEN dealer for product information.

Management

- Centralized management software KVM over IP Matrix Manager (<u>CCKM</u>) allows users to easily administrator all KE devices with an intuitive web-based GUI Dual console operation controls your system from both the transmitter's and receiver's keyboard, monitor, and mouse consoles
- OSD (On Screen Display) on the receiver configures both units
- EDID ExpertTM selects optimum EDID settings for smooth power-up and highest quality display Four selectable access modes for multiple simultaneous access (Exclusive/Occupy/Share/ View only mode) administrators can select access modes of permissions on Tx devices to boost collaboration or to avoid interference among users

 Command line interface – administrators can control all KVM over IP extenders via RS-232 or TCP/IP using a CLI or 3rd party application
- RS-232 serial ports allow users to connect to a serial terminal for TextMenu, CLI, or serial devices such as touch screens and barcode scanners
- Supports Hotkey Commands
- Flashing LED and beeping features help locate and identify devices
 Video Compression Level allows users to increase / decrease the video quality to adjust for appropriate network bandwidth
- Compatible with all KE devices

Security

- Dedicated LAN port for KE direct connections can be isolated from the corporate network
- Secure data transmission AES 128-bit encryption to secure all data before transmitted over a network and decrypts the data on the receiver
- Supports industry standard Transport Layer Security (TLS) protocol

Virtual Media

- USB Storage Transmission mode enhances data transmission performance, ideally for file transfers, OS patching, software installations and diagnostic testing
 Supports USB 2.0 DVD/CD drives, USB mass storage devices, PC hard drives and ISO images
- Supports Smart Card/CAC Reader




Specifications

Connectors	
USB Port	N/A
Console Ports	2 x USB Type A Female (White) 1 x DVI-D Female (White) 1 x Mini Stereo Jack (Green) 1 x Mini Stereo Jack (Pink) 1 x DB-9 Male (Black)
KVM Ports	1 x USB Type B Female (White) 1 x DVI-D Female (White) 1 x Mini Stereo Jack (Green) 1 x Mini Stereo Jack (Pink) 1 x DB-9 Female (Black)
Power	2 x DC Jack (Black)
LAN Ports	1 x RJ-45 (Black) 1 x SFP Slot
Switches	
OSD	N/A
Video	N/A
Graphics	N/A
Reset	1 x Semi-recessed Pushbutton
Mode Selection	1 x Slide Switch (Auto, RS-232 Config/Access Control, Local)
LEDs	
10/100/1000 Mbps	1 (10: Orange / 100: Orange & Green / 1000: Green)
Power	1 (Blue)
Local	1 (Green)
Remote	1 (Green)
Emulation	
Keyboard / Mouse	USB
Power Consumption	DC5V:10.02W:51BTU/h
	Note: ■ The measurement in Watts indicates the typical power consumption of the device with no external loading. ■ The measurement in BTU/h indicates the power consumption of the device when it is fully loaded.
Video Resolution	Up to 2560 x 2048 @ 50Hz/2560 x 1600 @ 60Hz
Latency	<5ms
Environmental	
Operating Temperature	0-50°C
Storage Temperature	-20-60°C
Humidity	0–95% RH, Non-condensing
Physical Properties	
Housing	Metal
Weight	1.13 kg (2.49 lb)
Dimensions (L x W x H)	21.50 x 16.33 x 4.18 cm (8.46 x 6.43 x 1.65 in.)
Note	For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.



Diagram



ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan Phone: 886-2-8692-6789 Fax: 886-2-8692-6767 www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.
ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
All rights reserved. All other trademarks are the property of their respective owners.