

VM7104

4-Port VGA Input Board



The VM7104 4-Port VGA Input Board offers an easy way to route 4 VGA video and audio sources up to 16 displays, when used in combination with the ATEN Modular Matrix Switch. The VM7104 supports RGBHV / RGBS/ Y CbCr/ YPbPr input signals; stereo audio that can be embedded into HDMI Audio output. The board is built with a hot-swappable design that is compatible with the <u>VM1600</u>, so that the unit doesn't need to be powered off when the board is changed.

Features

- Connects up to 4 VGA or Component inputs
- Supports RGBHV / RGBS/ YCbCr/ YPbPr input signals
- Hot-swappable design for easy integration of I/O boards
- Compatible with the VM1600 and can be mixed with any modular output boards for optimum flexibility



Specifications

| Video Input | |
|---------------------------|--|
| Interfaces | 4 x HDB-15 Female (Blue) |
| Impedance | 75 Ω |
| Max. Bandwidth | 300 MHz |
| Max. Resolution | Up to 1920 x 1200 |
| Max. Distance | 1.8 m |
| Audio Inputs | |
| Interfaces | 4 x Captive Screw Connectors, 5 pole * Audio signal type: stereo, balanced/unbalanced. |
| Power Consumption | 7.1W:33BTU/h |
| | Note: • The measurement in Watts indicates the typical power consumption of the device with no external loading. • The measurement in BTU/h indicates the power consumption of the device when it is fully loaded. |
| Environmental | |
| Operating Temperature | 0–40°C |
| Storage Temperature | -20–60°C |
| Humidity | 0 - 80% RH, Non-Condensing |
| Physical Properties | |
| Housing | Metal |
| Weight | 0.56 kg(1.23 lb) |
| Dimensions (L x W x H) | 35.20 x 23.80 x 2.33 cm (13.86 x 9.37 x 0.92 in.) |
| Note | Audio signal type support stereo, balanced/unbalanced. Balanced audio maximum input/output level: 0.5 Vrms (-6.02dBV@600 ohm) Unbalanced audio maximum input/output level: 1Vrms (0dBV@600ohm.) |
| Note | For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format. |
| | |



Diagram



ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan Phone: 886-2-8692-6789 Fax: 886-2-8692-6767 www.aten.com E-mail: marketing@aten.com

E

© Copyright 2015 ATEN® International Co., Ltd. ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd. All rights reserved. All other trademarks are the property of their respective owners.